



# JES smart/ECS Multi Gas Sensor

## Features

- Smart IoT enabled gas sensor
- Up to 4 electrochemical gas sensor modules (CO, NO, NO<sub>2</sub>, SO<sub>2</sub>)
- Installation in-situ (in the tunnel's driving area) or with suction line adapter
- Stainless steel housing 1.4404 (AISI 316L)
- IP rating IP69K
- Connection to tunnel control system by
  - MODBUS RTU (RS-485)
  - MODBUS/TCP (Ethernet)
  - Analogue and relay outputs
  - JSON Web service (Ethernet)
- Integrated web server for visualisation, configuration, data logging, remote maintenance (Ethernet option only)
- Optional smart/HUB IoT operating and control unit with touch display
- 

## System setup

- smart/ECS sensor to be mounted either
  - in-situ (directly in the tunnel's driving area) or
  - extractive in a niche, cross-cut, etc.
- Optional smart/HUB with touch display

## Operation

Gas monitoring during normal operation is used to control the tunnel ventilation at normal operation. If and with how much power artificial ventilation by jet fans is operated depends on the measured visibility and gas concentration. Electrochemical gas sensor cells induce currents proportional to the prevailing gas concentration. With these currents and the measured temperature, the gas sensor modules calculate the gas concentrations.

## Advantages

- Specifically designed for application in tunnels
- Single sensor instead of transmitter/receiver pair requiring exact alignment
- Low maintenance requirements, stable, accurate
- Pre-calibrated gas sensor modules for easy exchange
- Smart IoT enabled solution from sensor over hub to asset management
- Condition monitoring
- Remote maintenance
- Flexible integration into tunnel control system

## Application

Tunnels are important infrastructure elements in road networks and facilitate the connection of regions. Environmental conditions in tunnels are influenced by fog, particles and emissions and need to be monitored to protect people on their passage through the tunnel from danger and impacts on their health. Accidents in tunnels, and particularly fires, can have dramatic consequences and can prove extremely costly in terms of human life, increased congestion, pollution and repair costs. At every time people in the tunnel need to be supplied with breathable air and sufficient visibility.

Since 1990 JES Elektrotechnik GmbH develops, installs and maintains systems to monitor air characteristics and lighting conditions in tunnels. Our systems are robust, durable and resistant against the corrosive atmosphere in a tunnel. They operate reliably and have a high accuracy in measurement.

All systems fulfil the requirements of the EC guideline 2004/54/EC (Minimum safety requirements for tunnels in the trans-European road network) and the more detailed national guidelines and provisions:

- Austria: RVS 09.02 Tunnelausrüstung
  - Germany: RABT Richtlinien für die Ausstattung und den Betrieb von Straßentunneln
  - Switzerland: ASTRA Richtlinien und Fachhandbuch Betriebs- und Sicherheitsausrüstungen (BSA)
- Our range of products for tunnel covers systems for monitoring of
- Visibility (extractive or in-situ)
  - Toxic gases like CO, NO, NO<sub>2</sub> (extractive or in-situ)
  - Air velocity, direction and temperature
  - Luminance (access, threshold and interior zone)
  - Illuminance

## Technical Specifications

### Sensor device

<b>Sensor device smart/ECS (Standard variant)</b>	
Type	JES smart/ECS
Gas sensor ports	up to 3 (to be specified on order)
Power supply	24 VDC ± 10 %
Current consumption	max. 300 mA (@ 24 VDC)
Appliance class	Class III (PELV)
Material	Stainless steel 1.4404 (AISI 316L)
IP rating	IP 69K
Dimensions	160 x 160 x 100 mm
Weight	Approx. 2.5 Kg
Digital interfaces (standard)	MODBUS RTU (RS-485) MODBUS/TCP (Ethernet) Webserver for configuration (Ethernet)
Analogue/relay outputs (optional)	up to 2 <a href="#">analogue / relay output modules</a> , each: • 3 x 4 - 20 mA (2-wire, active) • 3 x relay
Temperature range	-40 .. +60 °C
Pressure range	900 .. 1100 hPa
Humidity range	15 .. 95% relative humidity (non-condensing)
Storage temperature	-40 .. +85 °C (without gas sensor modules)

<b>Sensor device smart/ECS-XL (XL variant)</b>	
Type	JES smart/ECS-XL
Gas sensor ports	up to 4 (to be specified on order)
Power supply	24 VDC ± 10 % AC option: 90 to 264 VAC, 48 to 62 Hz
Current consumption	max. 300 mA (@ 24 VDC)
Appliance class	Class III (PELV) Class I (AC option)
Material	Stainless steel 1.4404 (AISI 316L)
IP rating	IP 69K
Dimensions	250 x 160 x 100 mm
Weight	Approx. 2.5 Kg
Digital interfaces (standard)	MODBUS RTU (RS-485) MODBUS/TCP (Ethernet) Webserver for configuration (Ethernet)
Analogue/relay outputs (optional)	up to 2 <a href="#">analogue / relay output modules</a> , each: <html><ul> <li>3 x 4 - 20 mA (2-wire, active)</li> <li>3 x relay</li> </ul></html>
Temperature range	-40 .. +60 °C
Pressure range	900 .. 1100 hPa
Humidity range	15 .. 95% relative humidity (non-condensing)
Storage temperature	-40 .. +85 °C (without gas sensor modules)

### Gas sensor modules

<b>Gas sensor module CO-500</b>	
Type	JES smart/ECS-CO-500
Measuring method	Electrochemical cell
Measured value	Gas concentration in ppm
Measuring range	Configurable within 0 .. 500 ppm CO typically 0 .. 300 ppm CO
Maximum overload	1,000 ppm CO
Lower detectable limit	3 ppm CO
Resolution	0.1 ppm CO
Accuracy	$\pm 2$ ppm or 2 % reading <sup>1)</sup>
Temperature compensation	yes
T90 time	< 40 s
Long term drift	< 2 % signal loss per month
Expected operation life	3 years in air
Storage life	6 months in packaging
Storage temperature	5 .. 20 °C

<b>Gas sensor module NO2-2</b>	
Type	JES smart/ECS-NO2-2
Measuring method	Electrochemical cell
Measured value	Gas concentration in ppm
Measuring range	Configurable within 0 .. 2 ppm NO <sub>2</sub> typically 0 .. 2 ppm NO <sub>2</sub>
Maximum overload	10 ppm NO <sub>2</sub>
Lower detectable limit	0.05 ppm NO <sub>2</sub>
Resolution	0.02 ppm NO <sub>2</sub>
Accuracy	$\pm 0.05$ ppm or 5 % reading <sup>2)</sup>
Temperature compensation	yes
T90 time	< 60 s
Long term drift	< 2 % signal loss per month
Expected operation life	2 years in air
Storage life	6 months in packaging
Storage temperature	5 .. 20 °C

<b>Gas sensor module NO2-20</b>	
Type	JES smart/ECS-NO2-20
Measuring method	Electrochemical cell
Measured value	Gas concentration in ppm
Measuring range	Configurable within 0 .. 20 ppm NO <sub>2</sub> typically 0 .. 10 ppm NO <sub>2</sub>
Maximum overload	200 ppm NO <sub>2</sub>
Lower detectable limit	0.5 ppm NO <sub>2</sub>
Resolution	0.05 ppm NO <sub>2</sub>
Accuracy	$\pm 0.5$ ppm or 2 % reading <sup>3)</sup>
Temperature compensation	yes
T90 time	< 60 s

Long term drift	< 2 % signal loss per month
Expected operation life	2 years in air
Storage life	6 months in packaging
Storage temperature	5 .. 20 °C

**Gas sensor module NO-100**

Type	JES smart/ECS-NO-100
Measuring method	Electrochemical cell
Measured value	Gas concentration in ppm
Measuring range	Configurable within 0 .. 100 ppm NO typically 0 .. 30 ppm NO
Maximum overload	200 ppm NO
Lower detectable limit	1 ppm NO
Resolution	0.05 ppm NO
Accuracy	± 0.5 ppm or 2 % reading <sup>4)</sup>
Temperature compensation	yes
T90 time	< 10 s
Long term drift	< 2 % signal loss per month
Expected operation life	3 years in air
Storage life	6 months in packaging
Storage temperature	5 .. 20 °C

**Gas sensor module NO-25**

Type	JES smart/ECS-NO-25
Measuring method	Electrochemical cell
Measured value	Gas concentration in ppm
Measuring range	Configurable within 0 .. 25 ppm NO overload up to 0 .. 30 ppm NO
Maximum overload	50 ppm NO
Lower detectable limit	0.2 ppm NO
Resolution	0.05 ppm NO
Accuracy	± 0.2 ppm or 2 % reading <sup>5)</sup>
Temperature compensation	yes
T90 time	< 10 s
Long term drift	< 2 % signal loss per month
Expected operation life	3 years in air
Storage life	6 months in packaging
Storage temperature	5 .. 20 °C

**Analogue / relay output module****Analogue / relay output module ARO**

Type	JES smart/CORE-ARO
Analogue outputs	3 x 4 - 20 mA
Analogue output type	2-wire, active
Relay outputs	3 x SPST-NO

Max. contact rating	60 W (30 VDC, 2 A)
---------------------	--------------------

## 2.4" Touch display

2.4" Internal touch display D2	
Type	JES smart/CORE-D2
Display type	TFT colour
Diagonal screen size	2.4" (60.96 mm)
Display area	49.96 x 37.72 mm
Resolution	320 x 240 px
Touch type	capacitive
Backlight	LED - white

## Temperature Sensor

smart/ECS-TMP Temperature sensor option	
Type	JES smart/ECS-TMP
Temperature sensor	Pt1000 DIN B, $R_0$ : 1000 $\Omega$ , Temperature coefficient: $3.850 \times 10^{-3}/^\circ\text{C}$ , Standard: DIN EN 60751
Sensor sleeve material	Stainless steel 1.4571 (AISI 316Ti)
Cable material	Silicon
IP rating	IP 67
Cable length	30 cm (longer on request)
Temperature range	-60 .. +180 °C
Humidity range	5 .. 95% relative humidity (non-condensing)
Storage temperature	-30 .. +70 °C

## Conformities

Conformities	
Electrical standards	2014/35/EU Low Voltage Directive (LVD) 2014/30/EU Electromagnetic compatibility (EMC) EN IEC 61000-6-2:2019 Immunity standard for industrial environments EN IEC 61000-6-3:2007 + A1: 2011 Emission standard for residential, commercial and light-industrial environments EN 61010-1 Safety requirements for electrical equipment for measurement, control and laboratory use EN 61326-1 Electrical equipment for measurement, control and laboratory use - EMC requirements
Tunnel safety standards	AT: RVS 09.02.22 DE: RABT 2006 CH: ASTRA RL 13001, Fachhandbuch BSA NO: Norwegian Public Roads Administration Handbook No. 021 Road Tunnels
Gas monitoring	EN 50545-1 AT: ÖNORM M9418, ÖNORM M9419 DE: VDI 2053

## Document Revision

Page	status	user	datetime	revision	version
en:datasheets:smartecs	draft			1693426503	

[CSV Export](#)

1) , 2) , 3) , 4) , 5)

whichever is greater