



JES smart/ECS Multi Gas Sensor

Features

- Smart IoT enabled gas sensor
- Up to 4 electrochemical gas sensor modules (CO, NO, NO₂, SO₂)
- Installation in-situ (in the tunnel's driving area) or with suction line adapter
- Stainless steel housing 1.4404 (AISI 316L)
- IP rating IP69K
- Connection to tunnel control system by
 - MODBUS RTU (RS-485)
 - MODBUS/TCP (Ethernet)
 - Analogue and relay outputs
 - JSON Web service (Ethernet)
- Integrated web server for visualisation, configuration, data logging, remote maintenance (Ethernet option only)
- Optional smart/HUB IoT operating and control unit with touch display
-

System setup

- smart/ECS sensor to be mounted either
 - in-situ (directly in the tunnel's driving area) or
 - extractive in a niche, cross-cut, etc.
- Optional smart/HUB with touch display

Operation

Gas monitoring during normal operation is used to control the tunnel ventilation at normal operation. If and with how much power artificial ventilation by jet fans is operated depends on the measured visibility and gas concentration. Electrochemical gas sensor cells induce currents proportional to the prevailing gas concentration. With these currents and the measured temperature, the gas sensor modules calculate the gas concentrations.

Advantages

- Specifically designed for application in tunnels
- Single sensor instead of transmitter/receiver pair requiring exact alignment
- Low maintenance requirements, stable, accurate
- Pre-calibrated gas sensor modules for easy exchange
- Smart IoT enabled solution from sensor over hub to asset management
- Condition monitoring
- Remote maintenance
- Flexible integration into tunnel control system

Application

Tunnels are important infrastructure elements in road networks and facilitate the connection of regions. Environmental conditions in tunnels are influenced by fog, particles and emissions and need to be monitored to protect people on their passage through the tunnel from danger and impacts on their health. Accidents in tunnels, and particularly fires, can have dramatic consequences and can prove extremely costly in terms of human life, increased congestion, pollution and repair costs. At every time people in the tunnel need to be supplied with breathable air and sufficient visibility.

Since 1990 JES Elektrotechnik GmbH develops, installs and maintains systems to monitor air characteristics and lighting conditions in tunnels. Our systems are robust, durable and resistant against the corrosive atmosphere in a tunnel. They operate reliably and have a high accuracy in measurement.

All systems fulfil the requirements of the EC guideline 2004/54/EC (Minimum safety requirements for tunnels in the trans-European road network) and the more detailed national guidelines and provisions:

- Austria: RVS 09.02

Tunnelausrüstung

- Germany: RABT Richtlinien für die Ausstattung und den Betrieb von Straßentunneln

- Switzerland: ASTRA Richtlinien und Fachhandbuch Betriebs- und Sicherheitsausrüstungen (BSA)

Our range of products for tunnel covers systems for monitoring of

- Visibility (extractive or in-situ)
- Toxic gases like CO, NO, NO₂ (extractive or in-situ)
- Air velocity, direction and temperature
- Luminance (access, threshold and interior zone)
- Illuminance

Technical Specifications

Sensor device

Sensor device smart/ECS (SH3 / WH3 housing option)

Type	smart/ECS	
Gas sensor ports	up to 3 (to be specified on order)	
Power supply	24 VDC $\pm$ 10 %	
Current consumption	max. 300 mA (@ 24 VDC)	
Appliance class	Class III (PELV)	
Material	Stainless steel 1.4404 (AISI 316L)	
IP rating	IP 69	
Dimensions	160 x 160 x 100 mm	
Weight	Approx. 2.5 Kg	
Digital interfaces (standard)	MODBUS RTU (RS-485) MODBUS/TCP (Ethernet) Webserver for configuration (Ethernet)	
Analogue/relay outputs (optional)	up to 2 analogue / relay output modules , each: 3 x 4 – 20 mA (2-wire, active) 3 x SPST-NO (max. 60 VDC / 25 VAC, max. 0.5 A)	
Temperature range	-40 .. +60 °C	
Pressure range	900 .. 1100 hPa	
Humidity range	15 .. 95% relative humidity (non-condensing)	
Storage temperature	-40 .. +85 °C (without gas sensor modules)	

Sensor device smart/ECS (SH4 / WH4 housing option)

Type	smart/ECS	
Gas sensor ports	up to 4 (to be specified on order)	
Power supply (Standard)	24 VDC $\pm$ 10 %	
Power supply (IPS option)	100 to 240 VAC, 50/60 Hz	
Supply voltage fluctuations (IPS option)	$\pm$ 10 %	
Current consumption	max. 300 mA (@ 24 VDC)	
Appliance class	Class III (PELV) Class I (IPS option)	
Material	Stainless steel 1.4404 (AISI 316L)	
IP rating	IP 69	
Dimensions	250 x 160 x 100 mm	
Weight	Approx. 2.5 Kg	
Digital interfaces (standard)	MODBUS RTU (RS-485) MODBUS/TCP (Ethernet) Webserver for configuration (Ethernet)	
Analogue/relay outputs (optional)	up to 2 analogue / relay output modules , each: 3 x 4 – 20 mA (2-wire, active) 3 x SPST-NO (max. 60 VDC / 25 VAC, max. 0.5 A)	
Indoor/Outdoor use	Indoor use (tunnel)	
Altitude (IPS option only)	up to 2,000 m	
Temperature range	-40 .. +60 °C	
Pressure range	900 .. 1100 hPa	
Humidity range	15 .. 95% relative humidity (non-condensing)	

Storage temperature	-40 .. +85 °C (without gas sensor modules)
Pollution degree (IPS option only)	4 (intended environment) / 2 (when cover removed)

Gas sensor modules

Gas sensor module CO-500

Type	smart/ECS-CO-500	
Measuring method	Electrochemical cell	
Measured value	Gas concentration in ppm	
Measuring range	Configurable within 0 .. 500 ppm CO typically 0 .. 300 ppm CO	
Maximum overload	1,000 ppm CO	
Lower detectable limit	< 0.5 ppm CO	
Resolution	0.1 ppm CO	
Accuracy	± 2 ppm or 2 % reading ¹⁾	
Temperature compensation	yes	
T90 time	< 40 s	
Long term drift	< 2 % signal loss per month	
Dimensions	Ø 38 x 74 mm	
Weight	88 g	
Expected operation life	3 years in air	
Storage life	6 months in packaging	
Storage temperature	5 .. 20 °C	

Gas sensor module NO2-2

Type	smart/ECS-NO2-2	
Measuring method	Electrochemical cell	
Measured value	Gas concentration in ppm	
Measuring range	Configurable within 0 .. 2 ppm NO ₂ typically 0 .. 2 ppm NO ₂	
Maximum overload	10 ppm NO ₂	
Lower detectable limit	0.05 ppm NO ₂	
Resolution	0.02 ppm NO ₂	
Accuracy	± 0.05 ppm or 5 % reading ²⁾	
Temperature compensation	yes	
T90 time	< 60 s	
Long term drift	< 2 % signal loss per month	
Dimensions	Ø 38 x 74 mm	
Weight	88 g	
Expected operation life	2 years in air	
Storage life	6 months in packaging	
Storage temperature	5 .. 20 °C	

Gas sensor module NO2-20

Type	smart/ECS-NO2-20	
Measuring method	Electrochemical cell	
Measured value	Gas concentration in ppm	
Measuring range	Configurable within 0 .. 20 ppm NO ₂ typically 0 .. 10 ppm NO ₂	
Maximum overload	200 ppm NO ₂	
Lower detectable limit	< 0.15 ppm NO ₂	
Resolution	0.05 ppm NO ₂	
Accuracy	± 0.5 ppm or 2 % reading ³⁾	
Temperature compensation	yes	
T90 time	< 60 s	
Long term drift	< 2 % signal loss per month	
Dimensions	Ø 38 x 74 mm	
Weight	88 g	
Expected operation life	2 years in air	
Storage life	6 months in packaging	
Storage temperature	5 .. 20 °C	

Gas sensor module NO-100

Type	smart/ECS-NO-100	
Measuring method	Electrochemical cell	
Measured value	Gas concentration in ppm	
Measuring range	Configurable within 0 .. 100 ppm NO typically 0 .. 30 ppm NO	
Maximum overload	200 ppm NO	
Lower detectable limit	1 ppm NO	
Resolution	0.05 ppm NO	
Accuracy	± 0.5 ppm or 2 % reading ⁴⁾	
Temperature compensation	yes	
T90 time	< 10 s	
Long term drift	< 2 % signal loss per month	
Dimensions	Ø 38 x 74 mm	
Weight	88 g	
Expected operation life	3 years in air	
Storage life	6 months in packaging	
Storage temperature	5 .. 20 °C	

Gas sensor module NO-25

Type	smart/ECS-NO-25 
Measuring method	Electrochemical cell
Measured value	Gas concentration in ppm
Measuring range	Configurable within 0 .. 25 ppm NO overload up to 0 .. 30 ppm NO
Maximum overload	50 ppm NO
Lower detectable limit	< 0.4 ppm NO
Resolution	0.05 ppm NO
Accuracy	± 0.2 ppm or 2 % reading ⁵⁾
Temperature compensation	yes
T90 time	< 10 s
Long term drift	< 2 % signal loss per month
Dimensions	Ø 38 x 74 mm
Weight	88 g
Expected operation life	3 years in air
Storage life	6 months in packaging
Storage temperature	5 .. 20 °C

Gas sensor module SO2-CF20

Typ	smart/ECS-SO2-CF20 
Measuring method	Electrochemical cell
Measured value	Gas concentration in ppm
Measuring range	0 - 30 ppm SO2
Maximum overload	100 ppm SO2
Resolution	< 0.1 ppm SO2
Accuracy	< 2 % measurement value
Inboard Filter	To remove effect from H2S and HCl (cross sensitivity)
T90 time	< 30 s
Long term drift	< 2 % signal loss per month
Dimensions	Ø 38 x 74 mm
Weight	88 g
Expected operation life	2 years in air
Storage life	6 months in packaging
Storage temperature	5 ... 20 °C

Analogue / relay output module

Analogue / relay output module ARO

Type	smart/CORE-ARO
Analogue outputs	3 x 4 - 20 mA
Analogue output type	2-wire, active
Relay outputs	3 x SPST-NO
Max. contact rating	max. 60 VDC / 25 VAC, max. 0.5 A

2.4" Touch display

2.4" Internal touch display D2

Type	smart/CORE-D2
Display type	TFT colour
Diagonal screen size	2.4" (60.96 mm)
Display area	49.96 x 37.72 mm
Resolution	320 x 240 px
Touch type	capacitive
Backlight	LED - white

Temperature sensor option

smart/ECS-TMP Temperature sensor option

Type	smart/ECS-TMP	
Temperature sensor	Pt1000 DIN B, R ₀ : 1000 Ω, Temperature coefficient: $3.850 \times 10^{-3}/^{\circ}\text{C}$, Standard: DIN EN 60751	
Sensor sleeve material	Stainless steel 1.4571 (AISI 316Ti)	
Cable material	Silicon	
IP rating	IP 67	
Cable length	30 cm (longer on request)	
Temperature range	-60 .. +180 °C	
Humidity range	5 .. 95% relative humidity (non-condensing)	
Storage temperature	-30 .. +70 °C	

Temperature and humidity sensor

Temperature and humidity sensor

Type	smart/CORE-TRH	
Measured values	Temperature, Relative humidity	
Calculated variables	Dew point, Frost point, Wet bulb temperature, Ice bulb temperature, Water vapour partial pressure, Mixture ratio, Absolute humidity, Specific enthalpy	
Measuring ranges	Temperature: -40 .. 80 °C Relative humidity: 0 .. 100 %	
Accuracy	Temperature: $\pm(0,2 \text{ °C} + 0,67 \% \cdot \text{abs (reading - 20 °C)})$ Relative humidity: -15 .. 40 °C: $\pm (1.3 + 0.3 \% \text{ reading}) \% \text{RH}$ for RH $\leq 90 \%$, $\pm 2.3 \% \% \text{RH}$ for RH $> 90 \%$ -40 .. 80 °C: $\pm (1.5 + 1.5 \% \text{ reading}) \% \text{RH}$	
Resolution	Temperature: 0.01 °C Relative humidity: 0.01 %RH	
T90 time	< 15 s with stainless steel grid filter at 20 °C	
Current consumption	3 mA	
Housing material	Stainless steel 1.4404 (AISI 316L)	

Conformities

Conformities	
Markings	 
Electrical standards	2014/35/EU Low Voltage Directive (LVD) 2014/30/EU Electromagnetic compatibility (EMC) EN IEC 61000-6-2:2019 Immunity standard for industrial environments EN IEC 61000-6-3:2007 + A1: 2011 Emission standard for residential, commercial and light-industrial environments EN 61010-1 Safety requirements for electrical equipment for measurement, control and laboratory use EN 61326-1 Electrical equipment for measurement, control and laboratory use - EMC requirements
Tunnel safety standards	Austria: RVS 09.02.22 Germany: RABT 2006 Switzerland: ASTRA RL 13001, Fachhandbuch BSA Norway: Norwegian Public Roads Administration Handbook No. 021 Road Tunnels International: ISO 23431 Measurement of road tunnel air quality
Gas monitoring	Europe: EN 50545-1 Austria: ÖNORM M9419 Germany: VDI 2053

1) , 2) , 3) , 4) , 5)
whichever is greater